# FARO Scanner Freestyle<sup>3D</sup> X

The extra accurate FARO Scanner Freestyle<sup>3D</sup> X for challenging scanning projects





## Extra accuracy

The verifiable accuracy of 1mm enables you to carry out highly challenging scanning projects.

## Automatic flash

The auto mode automatically activates and de-activates the built-in LED light depending on the existing light conditions.

#### Real-Time Point Cloud Visualization

The real-time point cloud visualization supports the intuitive data acquisition, even for untrained operators.

## Up to 8m<sup>3</sup> scanning volume

The extensive scan volume boosts productivity by reducing scan time.

## Best point filter

The best point filter minimizes the noise and allows to get optimum data quality.

## Optional on-site calibration

The device can be easily calibrated on-site ensuring high quality data. A PDF report with key data permits maximum and verifiable confidence in the acquired data.

## Extra accuracy for handheld laser scanning

The FARO Freestyle<sup>3D</sup> X is a top-quality high-accuracy handheld scanner for professionals. It quickly and reliably documents rooms, structures and objects in 3D and creates high-definition pointclouds. With its lightweight carbon fibre body, the hand scanner weighs less than a kilogramme and is therefore extremely portable and mobile. With extraordinary accuracy, it is suitable for all applications in which challenging projects must be quickly scanned from various perspectives. The 3D scan data can easily be imported into all commonly used software solutions for architecture, engineering, construction, accident reconstruction, forensics or industrial manufacturing.

## Most Common Applications

Architecture, Construction & Engineering, Forensics & Law Enforcement, Oil & Gas, Maritime, Virtual Reality, 3D Scanning Service Providers

## **Benefits**

- ▶ FARO certified accuracy
- Auto levelling
- ▶ Flexibility to work without artificial targets
- No extra power supply required
- Easy-to-use scanning software
- Seamless integration with FARO Laser Scanner Focus<sup>3D</sup> laser scan data, even in grey scale
- Worldwide service and support from local FARO facilities

# FARO Scanner Freestyle<sup>3D</sup> X





## Performance Specifications Freestyle<sup>3D</sup> X

Range	0.5 - 3m
Resolution @ 0.5m	Lateral: 0.2mm - 1mm Depth: 0.2mm
3D point accuracy/ whole scan accuracy <sup>1</sup>	<1.0mm
Typical lateral accuracy <sup>2</sup>	<1mm
Single image point density	Up to 45,000 points/m² in 0.5m distance Up to 10,500 points/m² in 1m distance
Recorded 3D points <sup>3</sup>	Up to 88,000 points/s, point cloud density increases with time
Best point filter <sup>4</sup>	Noise reduction of typically 40% when scanning the same object from different distances
Typical Noise (rms)	0,7mm @ 0,5m distance 0,75mm @ 1m distance 2,5mm @ 2m distance 5mm @ 3m distance
Eye safety	Class 1 laser
Lighting conditions <sup>5</sup>	Up to 10,000 Lux
Light source	Inbuilt auto LED flash
Scan volume	8.1m³
Typical field of view (HxW)	450mm x 530mm @ 0.5m 930mm x 1,100mm @ 1m 1,800mm x 2,000mm @ 2m 2,600mm x 2,900mm @ 3m
Typical angular field of view (HxW)	45°x56° @ 0.5m 45°x59° @ 1m 49°x54° @ 2m 49°x52° @ 3m

Exposure time	0.02ms - 10ms (auto exposure)
Texture color	24bit
Dimensions	260mm x 310mm x 105mm
Connectivity	USB 3.0
Weight	0.98Kg
Power supply	5W, USB3.0-powered
IP rating	IP 52*
Calibration	Optional in-field user calibration with supplied carbon fibre calibration plate
Operating temperature range	0 - 40°C
Operating humidity range	Non-condensing
Laser power	max. 800mW
Duration of pulse	<= 10ms
Wavelength	798-821nm

 $^{\rm 1}$  Measured on a 1m reference scale, in 1m distance, for a lateral scanner movement of 1m, using targets for distance measurement  $^{\rm 2}$  Measured in 0.5m-3m distance  $^{\rm 2}$ Point density depends on scanned surface and lighting conditions <sup>4</sup> Noise reduction for equal scan times at 0.5m, 1m, 2m and 3m distance from object <sup>5</sup> Limited range and point density in sunlight \* Dust protection 5. Water protection 2: Protection against dripping water whilst device in standard idle position with sensor side facing

## **Recommended System Requirements for Tablet**

Microsoft Windows 8.1 pro, 64-Bit 4th generation Intel® Core™ i5 256GB hard disc with 8GB RAM

Microsoft® Surface Pro 2 or 3 is a recommended device



















## To learn more, visit: www.faro.com/Scanner/sg

## FARO Singapore Pte Ltd (Asia Pacific Headquarters)

No. 3 Changi South Street 2, #01-01 Xilin Districentre Building B, Singapore 486548

Tel: +65.65111350 Fax: +65.65430111

Email: asia@faro.com

## FARO Business Technologies India Pvt Ltd

E-12, B-1 Extension, Mohan Cooperative Industrial Estate, Mathura Road, New Delhi-110044, India Tel: +91.11.46465656 Fax: +91.11.46465660 Toll-free: 1800.102.8456 Email: india@faro.com